

SKYJACK™ SJII SERIES

...the new generation

**Economical.
Sturdy.
Dependable.**

This new generation of mobile elevating work platforms gets the job done faster, better. The Skyjack SJII Series is surefooted, dependable and ideally suited for slab-type applications, both industrial and construction. It's battery-powered, and driveable at full height, which makes it economical to use for overhead maintenance needs—or wherever quick mobility and high reach requirements exist. Full access to all working components allows for quick, easy servicing, which means less down time and better return on your investment.

The SJII Series is small on cost, big on features

Take a look at these standard features:

- ◆ Driveable at full height
- ◆ Joystick controller
- ◆ Heavy-duty continuous top railing with mid-rail and 6" toeboards
- ◆ 3' roll out deck extension
- ◆ Button hole plate on access ladders, all steel deck construction
- ◆ Battery state-of-charge indicator
- ◆ 2 speed, two-wheel hydraulic drive
- ◆ 25% gradeability
- ◆ Fully automatic charger
- ◆ "Swing-out" drawers contain electric/hydraulic componentry
- ◆ Color-coded, numbered wiring system
- ◆ Hourmeter
- ◆ Audible descent alarm
- ◆ Free-wheeling valve
- ◆ Manual lowering valve
- ◆ Spring applied, hydraulically released parking brake
- ◆ Puncture proof, solid rubber, non-marking tires
- ◆ Forklift pockets and tie-down rings
- ◆ Comprehensive Operation, Parts & Service Manual
- ◆ ANSI and CSA compliance



Shown: SJII Model 3220

SKYJACK™

SJII SERIES



3' (0.91m) roll out deck extension provides larger work area and versatility.



"Swing-out" drawers permit full access to all hydraulic and electric components for easy service and maintenance.



All batteries and charger are conveniently located in one tray for fast and easy maintenance checks.



Narrow width allows SJII Model 3220 to pass through standard doorways and narrow aisles.



Joystick controller permits operator to control all functions from platform. Removable to prevent unauthorized use.

Specifications:

Model	Work Height (Nom.)	Raised Height (Nom.)	Lowered Height	O/A Width	O/A Length	% Gradeability	Capacity Lbs.† (kg)	Platform Size	Tire	Travel Speed mph	Lift Speed (sec)	Weight Lbs (kg)
3220	26' (7.9m)	20' (6.1m)	38" (0.97m)	32" (0.8m)	89" (2.26m)	25%	800†† (363kg)	28"x80" (.71x2.03m)	**	2 (3.2km/h)	29	3739 (1696kg)
4620	26' (7.9m)	20' (6.1m)	38" (0.97m)	46" (1.17m)	89" (2.26m)	25%	1100†† (499kg)	42"x80" (1.07x2.03m)	**	2 (3.2km/h)	35	3593 (1630kg)
4626	32' (9.8m)	26' (7.9m)	45" (1.14m)	46" (1.17m)	89" (2.26m)	25%	850†† (386kg)	42"x80" (1.07x2.03m)	**	2 (3.2km/h)	41	4178 (1895kg)
6826	32' (9.8m)	26' (7.9m)	52" (1.32m)	68" (1.73m)	99" (2.51m)	25%	1200††† (544kg)	57"x80" (1.45x2.03m)	***	2 (3.2km/h)	45	5020 (2277kg)
6832	38' (11.6m)	32' (9.8m)	56" (1.42m)	68" (1.73m)	99" (2.51m)	25%	1000 (454kg)	57"x80" (1.45x2.03m)	***	2 (3.2km/h)	50	5480 (2486kg)

†All roll-out and power deck extensions 300# (136kg) capacity ††Power deck ext. reduces overall capacity 100# (45k) †††Power deck ext. reduces overall capacity 200# (90kg)
 *Standard Hinged Railings on these models (4626, 6826 & 6832) will clear 6'8" openings) **16x4.00x8 solid rubber, non-marking tires ***23x10.5x12 foam filled

Optional Equipment:

This literature for illustrative purposes only. Consult Parts/Operating and Service Manual for proper operating and maintenance procedures. Work platforms have been tested to comply with applicable standards as interpreted by Skyjack, Inc. Specifications are subject to change without notice.

- Flashing Amber Light
- 800 Watt AC Generator
- 6' Power Deck Extension¹
- 5' Power Deck Extension²
- Additional Parking Brake
- Air Operation Package
- 110V GFI AC Outlet on Platform
- Movement Alarm
- Gas/Propane Power Package (n/a 3220)
- Kit for Power Pack (n/a 3220)
- Safety Belt Lanyard Attachment Ring
- Hinged Railing System (3220 & 4620)
- Spring-loaded Full Height Gate Entry
- 16x4.00x8 Solid Rubber, Black Tires
- "EE" Rated Package
- Tilt Alarm w/Drive/Lift Cutout
- "Shop Air" Line to Platform
- Proportional Control

¹Models 3220, 4620, 4626 only. ²Models 6826 & 6832 only.

Distributed By:



SKYJACK™

SKYJACK, INC.
 55 Campbell Rd., Guelph, Ontario N1H 1B9
 Phone: (519)837-0888 • (800)265-2738
 SALES FAX: (519)837-8104

SKYJACK CORP. (USA)
 3451 Swenson Ave., St. Charles, Illinois 60174
 Phone: (630)262-0005 • (800)2SKYJACK
 FAX: (630)262-0006