

OPTIONS AND ACCESSORIES

TZ™-34/20 TZ™-50

PLATFORM OPTIONS		
PLATFORM ROTATION	•	•
POWER OPTIONS		
DC	•	•
HYBRID HONDA CHARGING SYSTEM		•
DRIVE OPTIONS		
DRIVE AND SET OPTION (ANSI/CSA/AUS)		•
DRIVE ONLY (CE)		•
COUPLER OPTIONS		
COMBINATION HITCH AND ADJUSTABLE HEIGHT COUPLER SYSTEM	•	•
2 IN (5.08 CM) BALL COUPLER	•	•
2.31 IN (5.87 CM) BALL COUPLER	•	•
2.5 IN (6.35 CM) I.D. PINTLE RING COUPLER – US	•	•
CLEVIS COUPLER – US	•	•
ACCESSORIES		
TOOL TRAY	•	•
FLUORESCENT TUBE CADDY	•	•
BATTERY CHARGE INDICATOR (BCI)	•	•
OPERATIONAL WARNING LIGHT PACKAGE (FLASHING BEACONS)	•	•
NON-MARKING OUTRIGGER FOOTPADS	•	•
SPARE TIRE	•	•
WHEEL CHOCKS	•	•
HORN	•	
LADDER		•
BICYCLE GUARD (CE)	•	•



SPECIFICATIONS

TRAILER-MOUNTED Z™-BOOMS

MODEL	WORKING HEIGHT		HORIZONTAL REACH		LIFT CAPACITY*							
					STANDARD PLATFORM				WITH PLATFORM ROTATION			
					ANSI/CSA		CE/AUS		ANSI/CSA		CE/AUS	
	US	Metric	US	Metric	US	Metric	US	Metric	US	Metric	US	Metric
TRAILER-MOUNTED Z™-BOOMS												
TZ™-34/20	40 ft	12.36 m	18 ft 4 in	5.59 m	500 lbs	227 kg	440 lbs	200 kg	460 lbs	209 kg	400 lbs	181 kg
TZ™-50	55 ft 6 in	17.09 m	29 ft 2 in	8.89 m	500 lbs	227 kg	440 lbs	200 kg	500 lbs	227 kg	440 lbs	200 kg

*Lift capacity varies depending on options and country standards.

