

ZOOMLION

ZS2032DC

BATTERY POWERED SCISSOR LIFT



FEATURES

Standard Features

- Proportional controls
- All motion alarm
- Fold-down handrails
- Flashing amber beacon
- Self-closing entry gate
- Emergency descent system
- Active pothole protection system
- Hour meter
- Forklift pockets
- Horn
- Drivable at full height
- Scissor maintenance prop
- Charging protection system
- Extension deck (unidirectional)
- Autobrake system
- On-board diagnostic
- Emergency stop button
- Over tilt protective system
- AC power to platform
- Load sensing system

Accessories & Options

- Air line to platform
- Platform work lights
- Maintenance-free battery
- Overhead protection bar

HIGHLIGHTS

High Performance

- Efficient electric direct drive system
- Greater platform capacity with better performance on-the-job
- Front-wheel drive and brake offer mobility and versatility

Easy Maintenance & Service

- Common components and modular design, easy to maintenance
- Bilateral swing-out trays (battery & hydraulic), simple to service
- Robust & build to last, reliable, and safe

ACCESS WITH ZOOMLION GREEN



ZS2032DC

Model	ZS2032DC
Size	
Work Height	26ft 3in
A-Platform Height-Elevated	19ft 8in
B-Platform Height-Stowed	3ft 8in
C-Platform Length	7ft 7in
D-Platform Width	2ft 8in
Platform Extension	3ft
E-Overall Height (Rails Up)	7ft 5in
Overall Height (Rails Down)	5ft 10in
F-Overall Length	8ft 2in
G-Overall Width	2ft 8in
H Wheelbase	6ft 1in
I-Ground Clearance (Stowed)	4.5in
J-Ground Clearance (Raised)	0.75in
Performance	
Platform Capacity	840lb
Capacity on Deck Extension	250lb
Max. Number of Workers	Indoor: 2 Outdoor: 1
Drive Speed (Stowed)	2.5mph
Drive Speed (Raised)	0.5mph
Turning Radius (Inside)	4in
Turning Radius (Outside)	6ft 11in
Lifting Motor	24V/3.3KW
Drive Motor	24V/2x0.75KW
Up/Down Time	28s/35s
Gradeability	30% (17°)
Max. Working Slope (Lateral/Vertical)	1.5°/3°
Control	Proportional Control
Drive	Front Wheels
Brake	Front Wheels
Tire	Ø15inx5in
Power	
Battery	4x6V/225Ah
Charger	24V/30A
Weight	
Gross	4280lb

