

# ZOOMLION

## ZS2242C

### CRAWLER SCISSOR LIFT



## FEATURES

### Standard Features

- Proportional controls
- All motion alarm
- Fold-down handrails
- Flashing beacon
- Self-closing entry gate
- Autobrake system
- Emergency descent system
- Emergency stop button
- On-board diagnostic
- Horn
- Over tilt protective system
- Hour meter
- Extension deck (unidirectional)
- Charging protection system
- Scissor maintenance prop
- Forklift pockets
- Load sensing system
- AC power to platform

### Accessories & Options

- Platform work lights
- Air line to platform
- Overhead protection bar
- Low-temperature hydraulic oil
- Synthetic biodegradable hydraulic oil

## HIGHLIGHTS

### High Performance

- Rubber crawler provides small ground pressure and great obstacle crossing ability
- Pivot steering with good maneuverability
- Simple single handle control for steering and walking
- Work height of 28ft 11in (8.8m) with high working efficiency

### Cost-Effectiveness

- Knuckles lubrication-free and maintenance-free
- AC motor full lifecycle maintenance-free

**ACCESS WITH ZOOMLION GREEN**



## ZS2242C

Model	ZS2242C
<b>Size</b>	
Work Height	28ft11in (8.80m)
A Platform Height- Elevated	22ft4in (6.80m)
B Platform Height- Stowed	3ft 8in (1.12m)
C Platform Length	6ft4in (1.94m)
D Platform Width	3ft1in (0.95m)
Platform Extension	3ft (0.91m)
E Overall Height (Rails Up)	7ft5in (2.26m)
Overall Height (Rails Down)	5ft10in (1.77m)
F Overall Length	6ft11in (2.1m)
G Overall Width	3ft5in (1.05m)
H Ground Clearance	4.5in (0.127m)
<b>Performance</b>	
Platform Capacity	5501b (250kg)
Capacity on Deck Extension	2501 (113kg)
Max. Number of Workers	2
Drive Speed (Stowed)	1.25mph (2km/h)
Drive Speed (Raised)	0mph (0km/h)
Turning Radius	0in (0m)
Drive Motor	24V/2x 1.8KW
Up/Down Time	34s/30s
Gradeability	30% (17°)
Max. Working Slope (Lateral/Vertical)	2°/2°
Drive	Rear Wheels
Brake	Rear Wheels
<b>Power</b>	
Battery	4x6V/220Ah
Charger	24V/30A
<b>Weight</b>	
Gross	3750lb (1700kg)

