ZOONLION VERTICAL MAST LIFTS ZMP09J

Comply with CE Standard

HIGHLIGHTS

- ► Large work range, leading in industry
- ▶ AC motor drive system, saving energy and maintenance free
- ▶ Mechanic pothole mechanism, easy to pass through
- ▶ Compact size with zero tailswing, easy to access narrow space
- ▶ Standard side fork hole, safe to transfer



Standard Features

Autobrake system	Flashing beacon
Proportional control	Active pothole protection system
All motion alarm	Horn
Charging protection system	Differential control
Self-closing entry gate	Hour meter
Maintenance-free battery	On-board diagnostic
Drivable at full height	Over tilt protective system
Emergency descent system	Forklift pockets
Emergency stop button	Load sensing system

Accessories & Options

- Platform work light
- AC power to platform
- ► GPS
- Remote monitor and rental management platform





Phone: 0086(731)-88353680 0086(731)-88250971 E-mail: awp@zoomlion.com Add: 701-Xulong Nan Lu, Xiangjiang New District, Changsha Hunan, China Web: www.zoomlion-access.com



ZOOMLION

Model	ZMP09J
Size	
Work Height	11.2m
Platform Height-Elevated	9.2m
Platform Horizontal Outreach	3.23m
Up and over Height	7.75m
A - Stowed Length	2.7m
B - Stowed Width	1m
C - Stowed Height	1.99m
D - Platform Length	0.76m
E - Platform Width	0.99m
F - Wheelbase	1.2m
G - Ground Clearance (Stowed)	0.065m
H - Ground Clearance (Raised)	0.015m
Performance	
Platform Capacity	200kg
Max. Number of Workers(indoor/outdoor)	2/1
Drive Speed (Stowed)	4.5km/h
Drive Speed (Raised)	0.5km/h
Turning Radius (Inside)	0.2m
Turning Radius (Outside)	1.61m
Lifting Motor	24V/3KW
Drive Motor	24V/2×0.7KW
Up/Down Time	42/40s
Gradeability	25% (14°)
Max. Working Slope(Lateral/Vertical)	2.5°
Control	Proportional control
Drive	Rear wheels
Tire	Solid seamless tire
Power	
Battery	4×6V/240Ah
Charger	24V/30A
Weight	
Gross	2990kg







